



## CT500g

<b>Cabinet Color</b>	Beige
<b>CRT</b>	Size ( Diagonal): 15" ( 38.1cm ) Dot Pitch: 0.24mm(H), 0.28mm(D) FST
<b>Viewable Image Size (Diagonal)</b>	13.8" ( 35.1 cm )
<b>Pre-set Display Area</b>	260mm x 195mm
<b>Signal Input</b>	Video: 0.7Vp-p, RGB analog Separate Sync.: TTL Level H/V Sync.: Positive / Negative
<b>Compatibility</b>	VESA, XGA, SVGA, VGA Mac® Equipped With VGA Port
<b>Scan Frequency</b>	Horizontal: 30K~56KHz Vertical: 50 ~120Hz
<b>Pixel Frequency</b>	65MHz
<b>Max. Resolution:</b>	1024x768@60Hz
<b>Resolutions Supported</b>	640x350@70Hz, 720x400@70Hz, 640x480@60/72/75/85Hz, 800x600@60/72/75/85Hz, 1024x768@60Hz
<b>Factory Pre-set Mode</b>	5
<b>User Programmable Mode</b>	15
<b>Power Source</b>	Universal 100~240 Vac, 50Hz / 60Hz
<b>Power Consumption</b>	<75 Watts ( Max. )
<b>EPA ENERGY STAR®</b>	Yes
<b>Connectors</b>	RGB Signal: 15-pin D-sub Male (Attached) Power: 3-Pin Plug (CEE22)
<b>User Controls</b>	
Front Panel	Power Switch, Menu, Contrast/Right, Brightness/Left, Exit
OSD Function	Contrast, Brightness, H-size, H-center, V-size, V-center, Zoom, Pincushion, Pin-balance, Trapezoid, Rotation, 6500K, 9300K, User Color, Degaussing, Moire Reduce, Recall, Exit
OSD Languages	English, German, French, Spanish, Italian, & Portuguese
<b>Plug &amp; Play</b>	VESA DDC1/2B
<b>Regulation</b>	UL, FCC, FDA, CSA, CE
<b>Operating Conditions</b>	Temperature: 0~40°C (32~104°F) Humidity: 10~85%
<b>Weight</b>	Net: 25.3lbs ( 11.5 kg ); Gross: 28.6lbs ( 13 kgs )
<b>Dimensions ( WxHxD mm )</b>	Monitor: 360x362x387; Carton: 460x438x390
<b>Dimensions ( WxHxD inches)</b>	Monitor: 14.2x14.3x15.2; Carton: 18x17x15.4
<b>Loading Quantity w/o pallet</b>	40' HQ = 928 pcs
<b>Loading Quantity w/ pallet</b>	40' HQ = 792 pcs
<b>UPC Code</b>	685417101047

Note: Specifications are subject to change without notice.